


MBOMBE 4



QUANTUM

MBOMBE 4

MULTI-ROLE, HIGHLY DYNAMIC MINE-PROTECTED
ARMOURED VEHICLE



GENERAL SPECIFICATIONS

Crew	2+1+6
Kerb Weight	14 100 kg
Payload	1900 kg
Wheelbase	3300 mm
Combat Weight–GVM	16 000 kg
Construction	Monocoque Hull (Not Chassis based)
Max Speed–Road	140km/h (Burst speed)
Turning Circle	18 m kerb to kerb
Road Range	800 km
Engine	Turbo Diesel 6 Cylinder, Intercooled,336 kW, 1627 Nm
Power to Weight Ratio (kW/ton)	21kW/T @ 16 000 kg
Transmission	Automatic 6 speed
Diff Locks	Air Operated Front, Centre and Rear
Brakes	Pneumatic, disc, ABS standard
Tyres	16.00 R20
Air Conditioner	12kW
Electrical System	24V
Ballistic Protection (Crew Compartment)	STANAG 4569–Level 3
Ballistic Protection (Engine Compartment)	STANAG 4569–Level 3 (Grille only at 0°)
Blast Protection	STANAG 4569–Level 4a & 4b 50kg TNT – side blast

OPTIONS

Run Flat Inserts (RFI)
Central Tyre Inflation System (CTIS)
Radios, Intercom Systems
Battlefield Management Systems
Winch
NATO Standard Tow Hitch
Public Address System
Fire Suppression Systems
Roof Hatch and Various Turret Systems
CBRN protection kit
Vehicle Location and Tracking System
Add-on Protection Kit (Side Mirrors, Door Hinges, Windows)
Driver Assist Camera System
Add-on Armour Kits to Level 4
Winterisation Kit

LAND – SEA – AIR

Specifications subject to change without prior notice. Possession of this printed material does not constitute an offer and/or valid legal contract of any type between Paramount Group and the recipient.